




## OFFICIAL QUOTE

30KVA 240 VOLTS TO 460Y/266  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER



## 30KVA 240 VOLTS TO 460Y/266 VOLTS THREE PHASE ISOLATION TRANSFORMER



**\$4,630.50 CAD**

Three Phase Isolation Transformer with a capacity of 30kVA, transforming 240 Volts to 460Y/266 Volts

SKU: BA30C-P1/Z3

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 30kVA, transforming 240 Volts to 460Y/266 Volts



## OFFICIAL QUOTE

### 30KVA 240 VOLTS TO 460Y/266 VOLTS THREE PHASE ISOLATION TRANSFORMER



#### PRODUCT SPECIFICATIONS

|                            |                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------|
| Weight                     | 298 lbs                                                                                              |
| Phases                     | <a href="#">3</a>                                                                                    |
| kVA                        | <a href="#">30</a>                                                                                   |
| Connection                 | <a href="#">3Ph-DY-5T-SU</a>                                                                         |
| Primary Voltage            | <a href="#">240</a>                                                                                  |
| Primary Max Current        | <a href="#">72.17A</a>                                                                               |
| Primary Markings           | <a href="#">X1-X2-X3</a>                                                                             |
| Primary Terminals          | <a href="#">Pads</a>                                                                                 |
| Secondary Voltage          | <a href="#">460Y/266</a>                                                                             |
| Secondary Max Current      | <a href="#">37.65A</a>                                                                               |
| Secondary Markings         | <a href="#">H0-H1-H2-H3</a>                                                                          |
| Secondary Terminals        | <a href="#">Pads</a>                                                                                 |
| Primary Taps               | <a href="#">+/- 2 x 2.5%</a>                                                                         |
| Conductor Material         | <a href="#">Aluminum</a>                                                                             |
| BIL (Insulation) Level     | <a href="#">10kV</a>                                                                                 |
| Efficiency (@35% Load) %   | <a href="#">98.23% (DOE 2016/NRCan 2019)</a>                                                         |
| Impedance Range            | <a href="#">4.0 – 6.0%</a>                                                                           |
| Sound (db)                 | <a href="#">45</a>                                                                                   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>                                                                       |
| Enclosure Size             | <a href="#">E3R-6</a>                                                                                |
| Finish/Colour              | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>                                             |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| Temperatue Rise            | <a href="#">150°C</a>                                                                                |



## OFFICIAL QUOTE

**30KVA 240 VOLTS TO 460Y/266  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER**



|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| <b>Insuation Class</b>      | <a href="#">150°C</a>                                    |
| <b>Country/Manufacturer</b> | <a href="#">Canada/RPM</a>                               |
| <b>Finish/Colour</b>        | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a> |