


#### **OFFICIAL QUOTE**

### 37.5VA 600 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





### 37.5VA 600 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$3,338.50 CAD

Single Phase Isolation Transformer with a capacity of 37.5kVA, transforming 600 Volts to 115/230 Volts

**SKU:** SA37J-K1/Z3

**Categories:** <u>Isolation Transformers</u>

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 37.5kVA, transforming 600 Volts to 115/230 Volts



#### **OFFICIAL QUOTE**



# 37.5VA 600 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

#### **PRODUCT SPECIFICATIONS**

Weight	272 lbs
Phases	1
kVA	<u>37.5</u>
Connection	1Ph-2coil-5t-SD
Primary Voltage	600
Primary Max Current	62.5A
Primary Markings	H1-H2
Primary Terminals	#2-14 AWG
Secondary Voltage	115/230
Secondary Max Current	326.09A
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.20% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



#### **OFFICIAL QUOTE**



# 37.5VA 600 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey