

OFFICIAL QUOTE

3KVA 115 VOLTS TO 208Y/120 VOLTS THREE PHASE ISOLATION TRANSFORMER





3KVA 115 VOLTS TO 208Y/120 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$1,463.00 CAD

Three Phase Isolation Transformer with a capacity of 3kVA, transforming 115 Volts to 208Y/120 Volts

SKU: BC3A1-M

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 3kVA, transforming 115 Volts to 208Y/120 Volts



OFFICIAL QUOTE



3KVA 115 VOLTS TO 208Y/120 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 73 lbs |
| Phases | <u>3</u> |
| kVA | <u>3</u> |
| Connection | 3Ph-DY-3T-SU |
| Primary Voltage | 115 |
| Primary Max Current | 15.06A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 208Y/120 |
| Secondary Max Current | 8.33A |
| Secondary Markings | <u>H0-H1-H2-H3</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | +/- 1 x 5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>5.0 – 7.0%</u> |
| Sound (db) | 40 |
| Enclosure Type | NEMA 1 |
| Enclosure Size | E1-3 |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 115°C |



OFFICIAL QUOTE



3KVA 115 VOLTS TO 208Y/120 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class | 115°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |