




OFFICIAL QUOTE

450KVA 220 VOLTS TO 416Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



450KVA 220 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER



\$47,301.35 CAD

Three Phase Isolation Transformer with a capacity of 450kVA, transforming 220 Volts to 416Y/240 Volts

SKU: BC450C2-N/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 450kVA, transforming 220 Volts to 416Y/240 Volts



OFFICIAL QUOTE

450KVA 220 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	3350 lbs
Phases	3
kVA	450
Connection	3Ph-DY-5CT-SU
Primary Voltage	220
Primary Max Current	1180.94A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	416Y/240
Secondary Max Current	624.54A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	99.11% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

450KVA 220 VOLTS TO 416Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey