



450VA 600 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$35,107.13 CAD

Three Phase Isolation Transformer with a capacity of 450kVA, transforming 600 Volts to 415Y/240 Volts

SKU: BA450J-N2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 450kVA, transforming 600 Volts to 415Y/240 Volts



PRODUCT SPECIFICATIONS

Weight	3640 lbs
Phases	3
kVA	450
Connection	3Ph-DY-5CT-SD
Primary Voltage	600
Primary Max Current	433.01A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	415Y/240
Secondary Max Current	626.04A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	99.11% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

450VA 600 VOLTS TO 415Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey