



45KVA 208 VOLTS TO 460Y/266 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$5,439.00 CAD

Three Phase Isolation Transformer with a capacity of 45kVA, transforming 208 Volts to 460Y/266 Volts

SKU: BA45B-P1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 45kVA, transforming 208 Volts to 460Y/266 Volts



PRODUCT SPECIFICATIONS

Weight	390 lbs
Phases	3
kVA	45
Connection	3Ph-DY-5T-SU
Primary Voltage	208
Primary Max Current	124.91A
Primary Markings	X1-X2-X3
Primary Terminals	300 MCM – 6
Secondary Voltage	460Y/266
Secondary Max Current	56.48A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.40% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

45KVA 208 VOLTS TO 460Y/266
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey