

OFFICIAL QUOTE

45KVA 220 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER





45KVA 220 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$5,494.94 CAD


Three Phase Isolation Transformer with a capacity of 45kVA, transforming 220 Volts to 380Y/220 Volts

SKU: BA45C2-R/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 45kVA, transforming 220 Volts to 380Y/220 Volts



OFFICIAL QUOTE



45KVA 220 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	390 lbs
Phases	<u>3</u>
kVA	45
Connection	3Ph-DY-5T-SU
Primary Voltage	220
Primary Max Current	118.09A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>300 MCM - 6</u>
Secondary Voltage	380Y/220
Secondary Max Current	68.37A
Secondary Markings	<u>H0-H1-H2-H3</u>
Secondary Terminals	300 MCM - 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	<u>Aluminum</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.40% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE



45KVA 220 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey