**OFFICIAL QUOTE**

**45KVA 415 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER**



# 45KVA 415 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

## $5,177.93 CAD

Three Phase Isolation Transformer with a capacity of 45kVA, transforming 415 Volts to 416Y/240 Volts

**SKU:** BA45G2-N/Z3
**Categories:** Isolation Transformers

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







Three Phase Isolation Transformer with a capacity of 45kVA, transforming 415 Volts to 416Y/240 Volts

**OFFICIAL QUOTE**

# 45KVA 415 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Weight** | 390 lbs |
| **Phases** | 3 |
| **kVA** | 45 |
| **Connection** | 3Ph-DY-5T-SU |
| **Primary Voltage** | 415 |
| **Primary Max Current** | 62.6A |
| **Primary Markings** | X1-X2-X3 |
| **Primary Terminals** | #2-14 AWG |
| **Secondary Voltage** | 416Y/240 |
| **Secondary Max Current** | 62.45A |
| **Secondary Markings** | H0-H1-H2-H3 |
| **Secondary Terminals** | #2-14 AWG |
| **Primary Taps** | +/- 2 x 2.5% |
| **Conductor Material** | Aluminum |
| **BIL (Insulation) Level** | 10kV |
| **Efficiency (@35% Load) %** | 98.40% (DOE 2016/NRCan 2019) |
| **Impedance Range** | 4.0 – 6.0% |
| **Sound (db)** | 45 |
| **Enclosure Type** | NEMA 3R Indoor |
| **Enclosure Size** | E3R-6 |
| **Finish/Colour** | Polyester Powder Coat – ANSI/ASA 61 Grey |
| **Standards & Certifications** | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| **Temperatue Rise** | 150°C |

**OFFICIAL QUOTE**

**45KVA 415 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER**

| | |
|---|---|
| **Insuation Class** | 150°C |
| **Country/Manufacturer** | Canada/RPM |
| **Finish/Colour** | Polyester Powder Coat – ANSI/ASA 61 Grey |