



## 500VA 380 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER

**\$44,578.80 CAD**

Three Phase Isolation Transformer with a capacity of 500kVA, transforming 380 Volts to 240Y/139 Volts

SKU: BA500F-S/Z3

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 500kVA, transforming 380 Volts to 240Y/139 Volts



PRODUCT SPECIFICATIONS

Weight	4098 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">500</a>
Connection	<a href="#">3Ph-DY-5CT-SD</a>
Primary Voltage	<a href="#">380</a>
Primary Max Current	<a href="#">759.67A</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">Pads</a>
Secondary Voltage	<a href="#">240Y/139</a>
Secondary Max Current	<a href="#">1202.81A</a>
Secondary Markings	<a href="#">X0-X1-X2-X3</a>
Secondary Terminals	<a href="#">Pads</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Aluminum</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">99.14% (DOE 2016/NRCAN 2019)</a>
Impedance Range	<a href="#">5.0 – 7.0%</a>
Sound (db)	<a href="#">60</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-10</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperature Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

500VA 380 VOLTS TO 240Y/139  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>