


#### **OFFICIAL QUOTE**

## 50KVA 347 VOLTS TO 480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 50KVA 347 VOLTS TO 480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$5,831.00 CAD

Single Phase Isolation Transformer with a capacity of 50kVA, transforming 347 Volts to 480 Volts

**SKU:** SC50E-H/Z3

**Categories:** <u>Isolation Transformers</u>

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 50kVA, transforming 347 Volts to 480 Volts



## **OFFICIAL QUOTE**



# 50KVA 347 VOLTS TO 480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

## **PRODUCT SPECIFICATIONS**

RODUCT SPECIFICATIONS		
Weight	348 lbs	
Phases	1	
kVA	<u>50</u>	
Connection	1Ph-2coil-5T-SU	
Primary Voltage	347	
Primary Max Current	144.09A	
Primary Markings	<u>X1-X2</u>	
Primary Terminals	300 MCM - 6	
Secondary Voltage	480	
Secondary Max Current	104.17A	
Secondary Markings	H1-H2	
Secondary Terminals	300 MCM - 6	
Primary Taps	+/- 2 x 2.5%	
Conductor Material	Copper	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	98.30% (DOE 2016/NRCan 2019)	
Impedance Range	4.0 - 6.0%	
Sound (db)	45	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	E3R-6	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



## **OFFICIAL QUOTE**



# 50KVA 347 VOLTS TO 480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	<u>150°C</u>
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey