

OFFICIAL QUOTE

50KVA 440 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





50KVA 440 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$5,522.30 CAD


Single Phase Isolation Transformer with a capacity of 50kVA, transforming 440 Volts to 460 Volts

SKU: SC50H2-H1/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 50kVA, transforming 440 Volts to 460 Volts



OFFICIAL QUOTE



50KVA 440 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| Weight | 348 lbs |
|----------------------------|--|
| Phases | 1 |
| kVA | 50 |
| Connection | 1Ph-2coil-5T-SU |
| Primary Voltage | 440 |
| Primary Max Current | <u>113.64A</u> |
| Primary Markings | <u>X1-X2</u> |
| Primary Terminals | 300 MCM - 6 |
| Secondary Voltage | 460 |
| Secondary Max Current | 108.7A |
| Secondary Markings | <u>H1-H2</u> |
| Secondary Terminals | <u>300 MCM – 6</u> |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | <u>Copper</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | 98.30% (DOE 2016/NRCan 2019) |
| Impedance Range | <u>4.0 - 6.0%</u> |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE



50KVA 440 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class | 150°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |