



5KVA 277 VOLTS TO 120/240 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$1,486.41 CAD

Single Phase Isolation Transformer with a capacity of 5kVA, transforming 277 Volts to 120/240 Volts

SKU: SC5D-K

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 5kVA, transforming 277 Volts to 120/240 Volts



PRODUCT SPECIFICATIONS

Weight	80 lbs
Phases	1
kVA	5
Connection	1Ph-1coil-3T-SD
Primary Voltage	277
Primary Max Current	18.05A
Primary Markings	H1-H2
Primary Terminals	#2-14 AWG
Secondary Voltage	120/240
Secondary Max Current	41.67A
Secondary Markings	X1-X2
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

5KVA 277 VOLTS TO 120/240 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey