



6KVA 220 VOLTS TO 440Y/254 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$2,046.10 CAD

Three Phase Isolation Transformer with a capacity of 6kVA, transforming 220 Volts to 440Y/254 Volts

SKU: BC6C2-P2

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 6kVA, transforming 220 Volts to 440Y/254 Volts



PRODUCT SPECIFICATIONS

Weight	116 lbs
Phases	3
kVA	6
Connection	3Ph-DY-3T-SU
Primary Voltage	220
Primary Max Current	15.75A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	440Y/254
Secondary Max Current	7.87A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

6KVA 220 VOLTS TO 440Y/254 VOLTS
THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey