

OFFICIAL QUOTE

6VA 240 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER





6VA 240 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$2,046.10 CAD


Three Phase Isolation Transformer with a capacity of 6kVA, transforming 240 Volts to 575Y/332 Volts

SKU: BC6C-Q1

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 6kVA, transforming 240 Volts to 575Y/332 Volts



OFFICIAL QUOTE



6VA 240 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS		
Weight	116 lbs	
Phases	<u>3</u>	
kVA	<u>6</u>	
Connection	3Ph-DY-3T-SU	
Primary Voltage	240	
Primary Max Current	14.43A	
Primary Markings	<u>X1-X2-X3</u>	
Primary Terminals	#2-14 AWG	
Secondary Voltage	<u>575Y/332</u>	
Secondary Max Current	6.02A	
Secondary Markings	<u>H0-H1-H2-H3</u>	
Secondary Terminals	#2-14 AWG	
Primary Taps	+/- 1 x 5%	
Conductor Material	Copper	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	N/A	
Impedance Range	<u>5.0 - 7.0%</u>	
Sound (db)	40	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	E3R-4	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



OFFICIAL QUOTE



6VA 240 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER

-	Insuation Class	150°C
	Country/Manufacturer	Canada/RPM
	Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey