



## 7.5VA 110 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

**\$1,914.53 CAD**

Single Phase Isolation Transformer with a capacity of 7.5kVA, transforming 110 Volts to 230/460 Volts

SKU: SC7A2-L1

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 7.5kVA, transforming 110 Volts to 230/460 Volts

7.5VA 110 VOLTS TO 230/460 VOLTS  
SINGLE PHASE ISOLATION  
TRANSFORMER



## PRODUCT SPECIFICATIONS

Weight	128 lbs
Phases	<a href="#">1</a>
kVA	<a href="#">7.5</a>
Connection	<a href="#">1Ph-1coil-3T-SU</a>
Primary Voltage	<a href="#">110</a>
Primary Max Current	<a href="#">68.18A</a>
Primary Markings	<a href="#">X1-X2</a>
Primary Terminals	<a href="#">#2-14 AWG</a>
Secondary Voltage	<a href="#">230/460</a>
Secondary Max Current	<a href="#">32.61A</a>
Secondary Markings	<a href="#">H1-H2</a>
Secondary Terminals	<a href="#">#2-14 AWG</a>
Primary Taps	<a href="#">+/- 1 x 5%</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">5.0 – 7.0%</a>
Sound (db)	<a href="#">40</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-4</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperatue Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

7.5VA 110 VOLTS TO 230/460 VOLTS  
SINGLE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>