

OFFICIAL QUOTE

750KVA 115 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER





750KVA 115 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$70,542.15 CAD

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 115 Volts to 240Y/139 Volts

SKU: BC750A1-S/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 750kVA, transforming 115 Volts to 240Y/139 Volts



OFFICIAL QUOTE



750KVA 115 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS			
Weight	4795 lbs		
Phases	<u>3</u>		
kVA	750		
Connection	3Ph-DY-5CT-SU		
Primary Voltage	115		
Primary Max Current	3765.33A		
Primary Markings	<u>X1-X2-X3</u>		
Primary Terminals	<u>Pads</u>		
Secondary Voltage	240Y/139		
Secondary Max Current	1804.22A		
Secondary Markings	<u>H0-H1-H2-H3</u>		
Secondary Terminals	<u>Pads</u>		
Primary Taps	+/- 2 x 2.5%		
Conductor Material	Copper		
BIL (Insulation) Level	<u>10kV</u>		
Efficiency (@35% Load) %	99.23% (DOE 2016/NRCan 2019)		
Impedance Range	<u>5.0 - 7.0%</u>		
Sound (db)	64		
Enclosure Type	NEMA 3R Indoor		
Enclosure Size	E3R-11		
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey		
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered		
Temperatue Rise	150°C		



OFFICIAL QUOTE



750KVA 115 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER

Insuation Class	<u>150°C</u>	-
Country/Manufacturer	Canada/RPM	
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey	