



## 750KVA 240 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

**\$58,522.10 CAD**

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 240 Volts to 220Y/127 Volts

**SKU:** BA750C-S2/Z3

**Categories:** [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 750kVA, transforming 240 Volts to 220Y/127 Volts



PRODUCT SPECIFICATIONS

|                            |  |
|----------------------------|--|
| Weight                     | 5000 lbs   |
| Phases                     | <a href="#">3</a>  |
| kVA                        | <a href="#">750</a>  |
| Connection                 | <a href="#">3Ph-DY-5CT-SD</a>  |
| Primary Voltage            | <a href="#">240</a>  |
| Primary Max Current        | <a href="#">1804.22A</a>   |
| Primary Markings           | <a href="#">H1-H2-H3</a>   |
| Primary Terminals          | <a href="#">Pads</a>   |
| Secondary Voltage          | <a href="#">220Y/127</a>   |
| Secondary Max Current      | <a href="#">1968.24A</a>   |
| Secondary Markings         | <a href="#">X0-X1-X2-X3</a>  |
| Secondary Terminals        | <a href="#">Pads</a>   |
| Primary Taps               | <a href="#">+/- 2 x 2.5%</a>   |
| Conductor Material         | <a href="#">Aluminum</a>   |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency (@35% Load) %   | <a href="#">99.23% (DOE 2016/NRCan 2019)</a>   |
| Impedance Range            | <a href="#">5.0 – 7.0%</a>   |
| Sound (db)                 | <a href="#">64</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure Size             | <a href="#">E3R-11</a>   |
| Finish/Colour              | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>   |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| Temperatue Rise            | <a href="#">150°C</a>  |

OFFICIAL QUOTE

750KVA 240 VOLTS TO 220Y/127  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER



|                      |  |
|----------------------|--|
| Insuation Class      | <a href="#">150°C</a>                                    |
| Country/Manufacturer | <a href="#">Canada/RPM</a>                               |
| Finish/Colour        | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a> |