



750KVA 415 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$53,570.23 CAD

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 415 Volts to 416Y/240 Volts

SKU: BA750G2-N/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 750kVA, transforming 415 Volts to 416Y/240 Volts



PRODUCT SPECIFICATIONS

Weight	5000 lbs
Phases	3
kVA	750
Connection	3Ph-DY-5CT-SU
Primary Voltage	415
Primary Max Current	1043.4A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	416Y/240
Secondary Max Current	1040.9A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	99.23% (DOE 2016/NRCan 2019)
Impedance Range	5.0 – 7.0%
Sound (db)	64
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-11
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

750KVA 415 VOLTS TO 416Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey