

750KVA 440 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$56,271.25 CAD

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 440 Volts to 380Y/220 Volts

SKU: BA750H2-R/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 750kVA, transforming 440 Volts to 380Y/220 Volts



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 5000 lbs |
| Phases | 3 |
| kVA | 750 |
| Connection | 3Ph-DY-5CT-SD |
| Primary Voltage | 440 |
| Primary Max Current | 984.12A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | Pads |
| Secondary Voltage | 380Y/220 |
| Secondary Max Current | 1139.51A |
| Secondary Markings | X0-X1-X2-X3 |
| Secondary Terminals | Pads |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Aluminum |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 99.23% (DOE 2016/NRCAN 2019) |
| Impedance Range | 5.0 – 7.0% |
| Sound (db) | 64 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-11 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperature Rise | 150°C |



OFFICIAL QUOTE

750KVA 440 VOLTS TO 380Y/220
VOLTS THREE PHASE ISOLATION
TRANSFORMER



| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |