



OFFICIAL QUOTE







750KVA 550 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$73,609.20 CAD

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 550 Volts to 230Y/133 Volts

SKU: BC750J2-S1/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 750kVA, transforming 550 Volts to 230Y/133 Volts



OFFICIAL QUOTE



750KVA 550 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

Weight	4795 lbs
Phases	<u>3</u>
kVA	750
Connection	3Ph-DY-5CT-SD
Primary Voltage	550
Primary Max Current	787.3A
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	230Y/133
Secondary Max Current	1882.66A
Secondary Markings	<u>X0-X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	99.23% (DOE 2016/NRCan 2019)
Impedance Range	<u>5.0 - 7.0%</u>
Sound (db)	64
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-11</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE



750KVA 550 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey