



## 750VA 575 VOLTS TO 550Y/318 VOLTS THREE PHASE ISOLATION TRANSFORMER

**\$52,647.00 CAD**

Three Phase Isolation Transformer with a capacity of 750kVA, transforming 575 Volts to 550Y/318 Volts

SKU: BA750J1-Q2/Z3

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 750kVA, transforming 575 Volts to 550Y/318 Volts



PRODUCT SPECIFICATIONS

Weight	5000 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">750</a>
Connection	<a href="#">3Ph-DY-5CT-SD</a>
Primary Voltage	<a href="#">575</a>
Primary Max Current	<a href="#">753.07A</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">Pads</a>
Secondary Voltage	<a href="#">550Y/318</a>
Secondary Max Current	<a href="#">787.3A</a>
Secondary Markings	<a href="#">X0-X1-X2-X3</a>
Secondary Terminals	<a href="#">Pads</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Aluminum</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">99.23% (DOE 2016/NRCan 2019)</a>
Impedance Range	<a href="#">5.0 – 7.0%</a>
Sound (db)	<a href="#">64</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-11</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperatue Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

750VA 575 VOLTS TO 550Y/318  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>