


#### **OFFICIAL QUOTE**

## 75KVA 550 VOLTS TO 200 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 75KVA 550 VOLTS TO 200 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$8,371.65 CAD


Single Phase Isolation Transformer with a capacity of 75kVA, transforming 550 Volts to 200 Volts

**SKU**: SC75J2-B1/Z3

**Categories:** <u>Isolation Transformers</u>

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 75kVA, transforming 550 Volts to 200 Volts



### **OFFICIAL QUOTE**



## 75KVA 550 VOLTS TO 200 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

### **PRODUCT SPECIFICATIONS**

Weight	444 lbs
Phases	1
kVA	<u>75</u>
Connection	1Ph-2coil-5t-SD
Primary Voltage	550
Primary Max Current	<u>136.36A</u>
Primary Markings	H1-H2
Primary Terminals	<u>300 MCM – 6</u>
Secondary Voltage	200
Secondary Max Current	375.0A
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	300 MCM - 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	<u>50</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



### **OFFICIAL QUOTE**



## 75KVA 550 VOLTS TO 200 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey