



OFFICIAL QUOTE

75KVA 575 VOLTS TO 208 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



75KVA 575 VOLTS TO 208 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$7,367.05 CAD

Single Phase Isolation Transformer with a capacity of 75kVA, transforming 575 Volts to 208 Volts

SKU: SC75J1-B/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 75kVA, transforming 575 Volts to 208 Volts



OFFICIAL QUOTE

75KVA 575 VOLTS TO 208 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	444 lbs
Phases	1
kVA	75
Connection	1Ph-2coil-5t-SD
Primary Voltage	575
Primary Max Current	130.43A
Primary Markings	H1-H2
Primary Terminals	300 MCM – 6
Secondary Voltage	208
Secondary Max Current	360.58A
Secondary Markings	X1-X2
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

75KVA 575 VOLTS TO 208 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey