


OFFICIAL QUOTE

75VA 575 VOLTS TO 120/240 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





75VA 575 VOLTS TO 120/240 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$7,032.19 CAD


Single Phase Isolation Transformer with a capacity of 75kVA, transforming 575 Volts to 120/240 Volts

SKU: SC75J1-K/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 75kVA, transforming 575 Volts to 120/240 Volts



OFFICIAL QUOTE



75VA 575 VOLTS TO 120/240 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

Weight	444 lbs
Phases	1
kVA	<u>75</u>
Connection	1Ph-2coil-5t-SD
Primary Voltage	<u>575</u>
Primary Max Current	130.43A
Primary Markings	H1-H2
Primary Terminals	300 MCM - 6
Secondary Voltage	120/240
Secondary Max Current	625.0A
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	300 MCM - 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	<u>50</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE



75VA 575 VOLTS TO 120/240 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey