

#### **OFFICIAL QUOTE**

# 9KVA 380 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER





# 9KVA 380 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$2,473.45 CAD


Three Phase Isolation Transformer with a capacity of 9kVA, transforming 380 Volts to 575Y/332 Volts

SKU: BC9F-Q1

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 9kVA, transforming 380 Volts to 575Y/332 Volts



#### **OFFICIAL QUOTE**



## 9KVA 380 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS		
Weight	132 lbs	
Phases	<u>3</u>	
kVA	9	
Connection	3Ph-DY-3T-SU	
Primary Voltage	380	
Primary Max Current	13.67A	
Primary Markings	<u>X1-X2-X3</u>	
Primary Terminals	#2-14 AWG	
Secondary Voltage	<u>575Y/332</u>	
Secondary Max Current	9.04A	
Secondary Markings	H0-H1-H2-H3	
Secondary Terminals	#2-14 AWG	
Primary Taps	<u>+/- 1 x 5%</u>	
Conductor Material	Copper	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	N/A	
Impedance Range	5.0 - 7.0%	
Sound (db)	40	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	E3R-4	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



#### **OFFICIAL QUOTE**



## 9KVA 380 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER

-	Insuation Class	150°C
	Country/Manufacturer	Canada/RPM
	Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey