



MC50H-C

\$2,084.21 USD

SKU: 5896e6945e4b

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|-----------------|---------------------------|
| Weight | 205 lbs |
| Phases | 1 |
| kVA | 50 |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 480 |



| | |
|----------------------------|--|
| Primary Max Current | 104.2A |
| Primary Markings | H0-H1 |
| Primary Terminals | #2/0-6 AWG |
| Secondary Voltage | 240 |
| Secondary Max Current | 208.3A |
| Secondary Markings | X0-X1 |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insuation Class | 220°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 2.5 – 4.5% |
| Sound (db) | 50 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-6 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |