

MP39J-M/BO/CLC

$12,631.00 CAD

SKU: 0f710a9e3102
Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	23.25	12.5	45.5	15.6	30	8	14.5	25.25



PRODUCT SPECIFICATIONS

Weight	315 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BAB
kVA	9
Connection	MPC3P-3t
Incoming Voltage	600
Primary Breaker	20A
Interruping Rating	14kAIC @ 600V
Output Voltage	208Y/120
Secondary Breaker	30A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
Insuation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	Copper
# of Circuits	18
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-1B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered