


OFFICIAL QUOTE

MP3A30H-M






MP3A30H-M


\$8,963.58 USD

SKU: 239a5c013483

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE MP3A30H-M



PRODUCT SPECIFICATIONS

Weight	710 lbs
Phases	<u>3</u>
Circuit Breaker Suitability	Eaton Type BR
kVA	30
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	80A
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	100A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	<u>+/- 2 x 2.5%</u>
Conductor Material	<u>Aluminum</u>
Insuation Class	200°C
Panel Board	Push-On
Load Center Bus Material	<u>Aluminum</u>
# of Circuits	<u>27</u>
Impedance	<u>1.5 - 3.0%</u>
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-3
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered