


MP3A45J-M

\$12,958.85 USD


SKU: 993f1e5c3259

Categories: [Mini Power Centers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	25.5	18	65.5	23.6	41.9	8	29.5	27.6





PRODUCT SPECIFICATIONS

Weight	960 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BR
kVA	45
Connection	MPC3P-5t
Incoming Voltage	600
Primary Breaker	90A
Interrupting Rating	14kAIC @ 600V
Output Voltage	208Y/120
Secondary Breaker	150A
Short Circuit Withstand	25kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
Insulation Class	200°C
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	30
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-4
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered