


OFFICIAL QUOTE MP3C15H-M






MP3C15H-M


\$10,738.00 CAD

SKU: 8629f33c94c5

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE MP3C15H-M



PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	475 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BR
kVA	<u>15</u>
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	40A
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	<u>50A</u>
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
Insuation Class	200°C
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	27
Impedance	<u>1.5 - 3.0%</u>
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-2
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered