

MP3C15H-M

$10,738.00 CAD

SKU: 8629f33c94c5
Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	23.25	14	52.5	16.1	36.5	8	19.3	25.4



PRODUCT SPECIFICATIONS

Weight	475 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BR
kVA	15
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	40A
Interruping Rating	14kAIC @ 480V
Output Voltage	208Y/120
Secondary Breaker	50A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
Insuation Class	200°C
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	27
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-2
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered