



MP3C15H-M \$7,908.21 USD

SKU: 8629f33c94c5 Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





The quote is valid 30 days from 18 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





PRODUCT SPECIFICATIONS

Weight	475 lbs
Phases	<u>3</u>
Circuit Breaker Suitability	Eaton Type BR
kVA	<u>15</u>
Connection	MPC3P-5t
Incoming Voltage	<u>480</u>
Primary Breaker	<u>40A</u>
Interruping Rating	<u>14kAIC @ 480V</u>
Output Voltage	<u>208Y/120</u>
Secondary Breaker	<u>50A</u>
Short Circuit Withstand	<u>10kAIC @ 240V</u>
Primary Taps	<u>+/- 2 x 2.5%</u>
Conductor Material	<u>Copper</u>
Insuation Class	<u>200°C</u>
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	27
Impedance	<u>1.5 – 3.0%</u>
Temperatue Rise	<u>130°C</u>
Enclosure	E3R-3PMPC-2
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered