


MP3C9J-M

\$8,573.00 CAD


SKU: 8137c13cf6f1

Categories: [Mini Power Centers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	18	12.5	43.5	15.6	27.9	8	14.5	20.1





PRODUCT SPECIFICATIONS

Weight	315 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BR
kVA	9
Connection	MPC3P-3t
Incoming Voltage	600
Primary Breaker	20A
Interrupting Rating	14kAIC @ 600V
Output Voltage	208Y/120
Secondary Breaker	30A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
Insulation Class	200°C
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	12
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-1
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered