



RA225J-C

\$9,899.00 CAD

SKU: 2cb8aaf28ae3
Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|------------|---------------------------|
| Weight | 115 lbs |
| Phases | 3 |
| kVA | 225 |
| Connection | 3PhA-NT-1 |



| | |
|----------------------------|--|
| Primary Voltage | 600 |
| Primary Max Current | 216.5A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | 600MCM-2 |
| Secondary Voltage | 240 |
| Secondary Max Current | 541.3A |
| Secondary Markings | X1-X2-X3 |
| Secondary Terminals | Pads |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insuation Class | 220°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 1.5 – 3.5% |
| Sound (db) | 50 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-8 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |