



RA45J-B \$3,331.79 USD

SKU: df0912b232a0 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 270 lbs |
|--------|-----------|
| Phases | <u>3</u> |
| kVA | <u>45</u> |

The quote is valid 30 days from 14 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





| Connection | <u>3PhA-NT-1</u> |
|----------------------------|---|
| Primary Voltage | 600 |
| Primary Max Current | <u>43.3A</u> |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>#2-14 AWG</u> |
| Secondary Voltage | 208 |
| Secondary Max Current | <u>124.9A</u> |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>300MCM-6</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insuation Class | <u>220°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>2.5 - 4.5%</u> |
| Sound (db) | <u>45</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | <u>E3R-6</u> |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |