



Categories: [Encapsulated Autotransformer](#)

A diagram illustrating a 3D network structure. It features six nodes labeled H1, X1, X2, H2, X3, and H3. The nodes are connected by wavy lines, forming a branching structure. H1 and X1 are at the top left, connected by a vertical line. X1 is connected to X3, which is connected to H3. X1 is also connected to X2, which is connected to H2. The nodes are arranged in a way that suggests a 3D spatial configuration.

Weight	400 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	480



Primary Max Current	18A
Primary Markings	H1-H2-H3
Primary Terminals	#2-14 AWG
Secondary Voltage	240
Secondary Max Current	36.1A
Secondary Markings	X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insuation Class	200°C
BIL (Insulation) Level	10kV
Impedance	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-3PEP-3
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered