



**RC30J-B**  
**\$2,764.71 USD**

SKU: 93ded26156e9  
 Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

|            |                           |
|------------|---------------------------|
| Weight     | 255 lbs                   |
| Phases     | <a href="#">3</a>         |
| kVA        | <a href="#">30</a>        |
| Connection | <a href="#">3PhA-NT-1</a> |



|                            |  |
|----------------------------|--|
| Primary Voltage            | <a href="#">600</a>  |
| Primary Max Current        | <a href="#">28.9A</a>  |
| Primary Markings           | <a href="#">H1-H2-H3</a>   |
| Primary Terminals          | <a href="#">#2-14 AWG</a>  |
| Secondary Voltage          | <a href="#">208</a>  |
| Secondary Max Current      | <a href="#">83.3A</a>  |
| Secondary Markings         | <a href="#">X1-X2-X3</a>   |
| Secondary Terminals        | <a href="#">#2/0-6 AWG</a>   |
| Primary Taps               | <a href="#">N/A</a>  |
| Conductor Material         | <a href="#">Copper</a>   |
| Insuation Class            | <a href="#">220°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency                 | <a href="#">N/A</a>  |
| Impedance                  | <a href="#">2.5 – 4.5%</a>   |
| Sound (db)                 | <a href="#">45</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure                  | <a href="#">E3R-5</a>  |
| Finish                     | <a href="#">Polyster Powder Coat – ANSI/ASA 61 Grey</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |