



RC45H-C/EP \$4,956.00 CAD

SKU: 52eba8f30273 Categories: Encapsulated Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 630 lbs |
|---------------------|------------------|
| Phases | <u>3</u> |
| kVA | <u>45</u> |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | <u>480</u> |
| Primary Max Current | <u>54.1A</u> |

The quote is valid 30 days from 6 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



RC45H-C/EP



| Primary Markings | <u>H1-H2-H3</u> |
|----------------------------|---|
| Primary Terminals | <u>#2-14 AWG</u> |
| Secondary Voltage | 240 |
| Secondary Max Current | <u>108.3A</u> |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>#2/0-6 AWG</u> |
| Primary Taps | <u>N/A</u> |
| Conductor Material | <u>Copper</u> |
| Insuation Class | <u>200°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Impedance | <u>0.5 – 1.5%</u> |
| Sound (db) | <u>45</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-5 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |