



RC75J-B/EP \$10,003.00 CAD

SKU: c9202abc1ef2 Categories: Encapsulated Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	830 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>600</u>

The quote is valid 30 days from 19 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Max Current	<u>72.2A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>#2/0-6 AWG</u>
Secondary Voltage	208
Secondary Max Current	<u>208.2A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>300MCM-6</u>
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insuation Class	<u>200°C</u>
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>0.5 – 1.5%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-3PEP-6
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered