



RC75J-C \$4,021.13 USD

SKU: d8d6155a6b88 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	400 lbs
Phases	<u>3</u>
kVA	75

The quote is valid 30 days from 19 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



RC75J-C



Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>600</u>
Primary Max Current	72.2A
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>#2/0-6 AWG</u>
Secondary Voltage	240
Secondary Max Current	<u>180.4A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>300MCM-6</u>
Primary Taps	Ν/Α
Conductor Material	Copper
Insuation Class	<u>220°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	<u>N/A</u>
Impedance	<u>1.5 – 3.5%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	<u>E3R-6</u>
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered