



## RC75J-H/EP \$2,825.10 USD

SKU: 7c2e6b2efe9b Categories: Encapsulated Autotransformer

## SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





## **PRODUCT SPECIFICATIONS**

Weight	560 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>600</u>
Primary Max Current	<u>72.2A</u>

The quote is valid 30 days from 20 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>#2/0-6 AWG</u>
Secondary Voltage	<u>480</u>
Secondary Max Current	<u>90.2A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>#2/0-6 AWG</u>
Primary Taps	<u>N/A</u>
Conductor Material	<u>Copper</u>
Insuation Class	<u>200°C</u>
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>0.5 – 1.5%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-3PEP-4
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered