

OFFICIAL QUOTE

RS125H






RS125H

\$2,221.00 CAD

SKU: dea648da1085

Categories: Motor Starters

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

Weight	170 lbs
Phases	3
НР	125
Connection	<u>3PhA-ST-0-3</u>
Primary Voltage	480
Primary Max Current	<u>150.4A</u>



OFFICIAL QUOTE

RS125H



Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	50/65/80/100%
Secondary Max Current	<u>1443.4A</u>
Secondary Markings	A-B-C-D
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Temperatue Rise	<u>150°C</u>
Insuation Class	220°C
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	N/A
Sound (db)	N/A
Enclosure Type	Core & Coil
Enclosure	N/A
Finish	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered