



SA15B-K/Z3 \$1,395.61 USD

SKU: e2ab568e7c36 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	145 lbs
Phases	1
kVA	<u>15</u>
Connection	<u>1Ph-2coil-5t-SD</u>
Primary Voltage	208
Primary Max Current	<u>72.1A</u>
Primary Markings	Н1-Н2

The quote is valid 30 days from 6 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





	1
Primary Terminals	<u>#2-14 AWG</u>
Secondary Voltage	120/240
Secondary Max Current	<u>125A</u>
Secondary Markings	<u>X1-X3-X2-X4</u>
Secondary Terminals	<u>#2-14 AWG</u>
Primary Taps	<u>+/-2 x 2.5%</u>
Conductor Material	Aluminum
Insuation Class	<u>220°C</u>
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>4.0 - 6.0%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-4
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Efficiency	<u>97.70%</u>
An and a second	