



SA15B-K/Z3 \$1,895.00 CAD

SKU: e2ab568e7c36 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	145 lbs
Phases	1
kVA	<u>15</u>
Connection	1Ph-2coil-5t-SD
Primary Voltage	208
Primary Max Current	<u>72.1A</u>
Primary Markings	<u>H1-H2</u>

The quote is valid 30 days from 22 December 2024. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Terminals	<u>#2-14 AWG</u>
Secondary Voltage	120/240
Secondary Max Current	<u>125A</u>
Secondary Markings	<u>X1-X3-X2-X4</u>
Secondary Terminals	<u>#2-14 AWG</u>
Primary Taps	<u>+/- 2 x 2.5%</u>
Conductor Material	Aluminum
Insuation Class	220°C
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>4.0 - 6.0%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	<u>E3R-4</u>
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Efficiency	<u>97.70%</u>