

SA15B-K2/Z3

$1,862.00 CAD

SKU: 90402b80c365
Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	145 lbs
Phases	1
kVA	15
Connection	1Ph-2coil-5t-SD
Primary Voltage	208
Primary Max Current	72.1A
Primary Markings	H1-H2

The quote is valid 30 days from 21 December 2024. The price does not include: "Special Features", freight and possible taxes.
Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.

Primary Terminals	#2-14 AWG
Secondary Voltage	110/220
Secondary Max Current	136.4A
Secondary Markings	X1-X3-X2-X4
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
Insuation Class	220°C
BIL (Insulation) Level	10kV
Impedance	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-4
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Efficiency	97.70%