



**SA15J-K/Z3**

**\$1,855.00 CAD**

SKU: 794957c4f07e

Categories: [Isolation Transformers](#)

## SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



## PRODUCT SPECIFICATIONS

|                     |                                 |
|---------------------|---------------------------------|
| Weight              | 145 lbs                         |
| Phases              | <a href="#">1</a>               |
| kVA                 | <a href="#">15</a>              |
| Connection          | <a href="#">1Ph-2coil-5t-SD</a> |
| Primary Voltage     | <a href="#">600</a>             |
| Primary Max Current | <a href="#">25A</a>             |
| Primary Markings    | <a href="#">H1-H2</a>           |



|                            |  |
|----------------------------|--|
| Primary Terminals          | <a href="#">#2-14 AWG</a>  |
| Secondary Voltage          | <a href="#">120/240</a>  |
| Secondary Max Current      | <a href="#">125A</a>   |
| Secondary Markings         | <a href="#">X1-X3-X2-X4</a>  |
| Secondary Terminals        | <a href="#">#2-14 AWG</a>  |
| Primary Taps               | <a href="#">+/- 2 x 2.5%</a>   |
| Conductor Material         | <a href="#">Aluminum</a>   |
| Insulation Class           | <a href="#">220°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Impedance                  | <a href="#">4.0 – 6.0%</a>   |
| Sound (db)                 | <a href="#">45</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure                  | <a href="#">E3R-4</a>  |
| Finish                     | <a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>   |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| Efficiency                 | <a href="#">97.70%</a>   |