




SC15B-K/Z3

\$1,366.89 USD

SKU: b7091626cbcb

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|----------------------------|---------------------------------|
| Weight | 160 lbs |
| Phases | 1 |
| kVA | 15 |
| Connection | 1Ph-2coil-5t-SD |
| Primary Voltage | 208 |
| Primary Max Current | 72.1A |
| Primary Markings | H1-H2 |



| | |
|---------------------------------------|--|
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 120/240 |
| Secondary Max Current | 125A |
| Secondary Markings | X1-X3-X2-X4 |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Copper |
| Insulation Class | 220°C |
| BIL (Insulation) Level | 10kV |
| Impedance | 4.0 – 6.0% |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-4 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Efficiency | 97.70% |