




The diagram illustrates a 2D array of 12 neurons arranged in two rows of six. The top row contains neurons labeled 1, 2, 3, 1, 2, 3. The bottom row contains neurons labeled H4, H2, H3, H3, H2, H1. Connections are shown as lines between neurons. Two groups of three neurons are highlighted at the top: X1 (neurons 1, 2, 3) and X2 (neurons 1, 2, 3). Three groups of four neurons are highlighted at the bottom: H4 (neurons 1, 2, 3, H4), H2 (neurons 2, 3, H2, H3), and H3 (neurons 3, 1, H3, H1). The connections show a complex network of interactions between these groups.



Primary Terminals	#2-14 AWG
Secondary Voltage	600
Secondary Max Current	12.5A
Secondary Markings	H1-H2
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
Insuation Class	220°C
BIL (Insulation) Level	10kV
Impedance	5.5 – 7.0%
Sound (db)	40
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-4
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Efficiency	N/A