

OFFICIAL QUOTE

2500KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER






2500KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER


\$10,860.50 USD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 208Y Volts to 220Y Volts

SKU: RA2500B-C2 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 2500kVA, transforming 208Y Volts to 220Y Volts



OFFICIAL QUOTE

2500KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	959 lbs
Phases	<u>3</u>
kVA	2500
Connection	<u>3PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	<u>6939.3A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	Pads
Secondary Voltage	220
Secondary Max Current	<u>6560.8A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>0.5 – 1.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

2500KVA 208 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM