


9KVA 480 VOLTS TO 208Y/120 VOLTS  
THREE PHASE ENCAPSULATED  
ISOLATION TRANSFORMER



## 9KVA 480 VOLTS TO 208Y/120 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER



**\$2,930.00 CAD**

Three Phase Encapsulated Isolation Transformer with a capacity of 9kVA, transforming 480 Volts to 208Y/120 Volts

SKU: BC9H-M/EP

Categories: [Encapsulated Isolation Transformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Encapsulated Isolation Transformer with a capacity of 9kVA, transforming 480 Volts to 208Y/120 Volts



9KVA 480 VOLTS TO 208Y/120 VOLTS  
THREE PHASE ENCAPSULATED  
ISOLATION TRANSFORMER

## PRODUCT SPECIFICATIONS

Weight	240 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">9</a>
Connection	<a href="#">3Ph-DY-3T-SD</a>
Primary Voltage	<a href="#">480</a>
Primary Max Current	<a href="#">10.8A</a>
Primary Markings	<a href="#">H1-H2-3</a>
Primary Terminals	<a href="#">#2-14 AWG</a>
Secondary Voltage	<a href="#">208Y/120</a>
Secondary Max Current	<a href="#">25A</a>
Secondary Markings	<a href="#">X0-X1-X2-X3</a>
Secondary Terminals	<a href="#">#2-14 AWG</a>
Primary Taps	<a href="#">+/- 1 x 5%</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">1.5 – 3.5%</a>
Sound (db)	<a href="#">40</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-3PEP-3</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>